Amendments to the Claims

This listing of the claims replaces all prior versions and listing of the claims in the present application.

Listing of Claims

1-35. (canceled)

36. (currently amended) Data A data network implemented by a first network level (104) having a first addressing scheme and at least a second network level (108) having a second addressing scheme, each network level provides connectivity over at least one network domain, the data network comprising: is characterised in that

a first group of Network Resource Managers, NRMs, (b-d)) is (b-d) that is arranged to control the resources of the first network level and a second group of NRMs (e-g) that is arranged to control the resources of the second network level,

wherein the NRMs of the first group (b-d) and second group (e-g) comprise means for communicating on a common network level and for exchanging resource requests by using the first addressing scheme, and

wherein the NRMs (e-g) of the second group further comprise means for performing an address mapping between the first and second addressing schemes.

37. (currently amended) Data The data network according to claim 36, wherein the first network level is the Internet

Protocol, IP, (IP) layer.

- 38. (currently amended) Data The data network according to claim 36, wherein the second network level is a link protocol layer.
- 39. (currently amended) Data The data network according to claim 37, wherein the second network layer level is a second protocol layer controlling an overlay network on top of said IP layer.
- 40. (currently amended) Data The data network according to claim 37, wherein the second network layer level is a second IP layer controlling an overlay network on top of said IP layer.
- 41. (currently amended) Data The data network according to claim 40, wherein it further comprises further comprising a third network level having a third addressing scheme, the resources of said third network level are protocol layer is controlled by a third group of NRMs comprising means for exchanging resource requests with NRMs of the first network level using the first addressing scheme.
- 42. (currently amended) $\frac{1}{2}$ $\frac{1}{2}$ The data network according to claim [[36]] $\frac{1}{4}$, wherein the NRMs of the third group further comprise means for performing an address mapping between the first and third addressing schemes.
- 43. (currently amended) $\frac{1}{2}$ $\frac{1}{2}$

protocol layer controlling an overlay network on top of said IP layer.

- 44. (currently amended) Data The data network according to claim 41, wherein the third network layer level is a second IP layer controlling an overlay network on top of said IP layer.
- 45. (currently amended) Data The data network according to claim 41, wherein the third network layer level is a third protocol layer controlling an overlay network on top of said IP layer.
- 46. (currently amended) Data The data network according to claim 41, wherein the third network layer level is a link protocol layer.
- 47. (currently amended) Data The data network according to claim 36, wherein the NRMs within at least one of said groups are arranged in a hierarchical structure arranged to communicate with each other.
- 48. (currently amended) Data The data network according to claim. 36, wherein each of the NRMs is a logically centralised centralized unit in a network.
- 49. (currently amended) Data The data network according to claim [[47]]48, wherein said logically centralised centralized unit is distributed or backed up over several physical servers
- 50. (currently amended) Data The data network according to claim 36, wherein the data network in at least one of the network

levels comprises a Network Controller (NC) comprising means for receiving a request from an NRM and means for obtaining detailed information such as including at least one of topology maps, traffic measurement information, and alarms of the network domain that is controlled by said NRM in response to said request.

- 51. (currently amended) Data The data network according to claim 49, wherein the data network in at least one of the network levels comprises a Device Controller (DC) comprising means for receiving a request from the NC and means for controlling vendor specific node technologies in response to said request.
- 52. (currently amended) Data The data network according to claim [[50]]51, wherein the DC is co-located with the NC in at least one of the network domains.
- 53. (currently amended) Method A method in a data network implemented by a first network level having a first addressing scheme and at least a second network level having a second addressing scheme, each network level provides connectivity over at least one network domain, the method comprising is characterised in that it comprises the steps of:

-controlling controlling (201) the resources of the first network level by a first group of Network Resource Managers, NRMs, and

-controlling controlling (202) the resources of the second network level by a second group of NRMs, wherein the first group

and the second group of NRMs comprises means for communicating on a common network level,

-exchanging exchanging (203) resource requests between NRMs of the first and second group by using the first addressing scheme, and

-performing performing (204) an address mapping between the first and second addressing schemes.

- 54. (currently amended) Method The method according to claim 53, wherein the first network level is the Internet Protocol, IP, (IP) layer.
- 55. (currently amended) Method The method according to claim 54, wherein the second network level is a link protocol layer.
- 56. (currently amended) <u>Method The method</u> according to claim 54, wherein the second network <u>layer level</u> is a second IP layer controlling an overlay network on top of said IP layer.
- 57. (currently amended) Method The method according to claim 54, wherein the second network layer level is a second protocol layer controlling an overlay network on top of the IP layer.
- 58. (currently amended) Method The method according to claim 53, wherein the data network further comprises a third network level having a third addressing scheme and the method comprises the further step of:

-controlling controlling the resources of said third network

level protocol layer by a third group of NRMs and

-exchanging exchanging resource requests between any of the NRMs of the first and second network level using the first addressing scheme.

- 59. (currently amended) Method The method according to claim 58, wherein it further comprises further comprising the step of: performing an address mapping between the first and third addressing schemes.
- 60. (currently amended) Method The method according to claim 59, wherein the third network layer level is a third protocol layer controlling an overlay network on top of the IP layer.
- 61. (currently amended) Method The method according to claim 59, wherein the third network layer level is a second IP layer controlling an overlay network on top of said IP layer.
- 62. (currently amended) Method The method according to claim 59, wherein the third network layer level is a link protocol layer.
- 63. (currently amended) Method The method according to claim 53, wherein the NRMs within at least one of said groups are arranged in a hierarchical structure arranged to communicate with each other.
- 64. (currently amended) Method The method according claim 53, wherein each of the NRMs is a logically centralised centralized unit in a network.
 - 65. (currently amended) Method The method according to claim

- 64, wherein said logically centralised <u>centralized</u> unit is distributed or backed up over several physical servers
- 66. (currently amended) Method The method according to claim 53, wherein the data network in at least one of the network levels comprises a Network Controller (NC), wherein the method comprises the further steps of:

-receiving receiving by the NC a request from an NRM and
-obtaining obtaining detailed information such as including
at least one of topology maps, traffic measurement information,
and alarms of the network domain that is controlled by said NRM
in response to said request.

67. (currently amended) Method The method according to claim 66, wherein the data network in at least one of the network levels comprises a Device Controller (DC), wherein the method further comprises the step of:

-receiving receiving by the DC a request from the NC and
-controlling controlling vendor specific node technologies
in response to said request.

- 68. (currently amended) Method The method according to claim 67, wherein the DC is co-located with the NC in the at least one of the network domains.
 - 69. (canceled)
- 70. (currently amended) A computer program product stored on a computer usable medium, comprising readable program for causing

Docket No. 1505-1078 Appln. No. 10/535,208

a computer, within a router or a server in [[a]] the data network to control an execution of the steps of claim 53.